IB BETAFENCE

Decofor[®] swing gate

Product detail



<u>Gates</u>

The Decofor single and double swing gates are a perfect combination with the decorative Decofor Arco and Recto panel fences.

BENEFITS

- The design is in perfect harmony with the Decofor panels Arco and Recto.
- Frame, infill and post system are of a very rigid construction.
- The limited accessories allow a quick installation.
- Decofor gates receive the best anti-corrosion coating available: the gates receive a protective coating, then a polyester coating that reaches the highest norms in the field of gloss, hardness and adhesion.

Frame

- The gate frame is made out of rectangular steel tube with a profile of 60 x 40 mm.
- Adjustable hinges allow the wings to be opened 180°.
- Lock systems composed of a lock slot, a counter lock, integrated lock with cylinder and handle.
- The double gates are supplied with a ground bolt to be anchored into the central floor plate.

Posts

- Profile : single gates : 80 x 80 x 3 mm
 - double gates: 100 x 100 x 3 mm

They are adapted to the different heights of fences and completed with a metal ball cap. They are supplied with inserts for the fixation of the fencing panels.

Panel infill frame

Decofor Arco panel with mesh of 200 x 65 mm is welded into the gate frame. Gates with Decofor Recto on request.

Accessoires

For wall fixation special hinges are available.

Coating technique

Galvanised and polyester coated.

aivailiseu allu

Colours Black RAL 9005

ASSORTMENT OF SWING GATES DECOFOR ARCO				
Width	Height	Free passage	Gate posts profile	Posts length
mm	mm	mm	mm	mm
Single Swing Gates				
1120	886	1040	80 x 80 x 3	1300
1120	1086	1040	80 x 80 x 3	1500
1120	1286	1040	80 x 80 x 3	1800
1120	1486	1040	80 x 80 x 3	2000
Double Swing Gates				
3720	886	3620	100 x 100 x 3	1300
3720	1086	3620	100 x 100 x 3	1500
3720	1286	3620	100 x 100 x 3	1800
3720	1486	3620	100 x 100 x 3	2000

Applications





Functionalities



www.betafence.com