

# CARRIER SLIDING DOOR SINGLE RAIL X2

The Carrier sliding door with 2 single rails can be built from our mesh or polycarbonate panels to fit your chosen machine guard system. The door is built using the standard panel height of 2,050 mm by combining panels in up to 5 widths. The parallel door blades run in separate aluminum rails at the top and hook into each other when opened. The panels and posts together with the top rail and door kit are supplied separately for assembly on site. Choose either the 60x40 mm or 80x80 mm posts for your solution. Depending on the risk assessment, you choose the preferred lock for your door; Cylinder Lock or the Troax Safe Lock or any other type of handle solution with or without a safety switch. The standard opening width is approximately 1,180 mm-2,780 mm.



## VARIANTS

Art. Nr	Components
36905610	Kit 5610 Carrier Singel

## ASSEMBLY INSTRUCTIONS





Assembly instruction - Carrier sliding door single rail x2 Kit  
36905610.pdf


 [Interactive 3D](#)

 [PDF](#)

## DOWNLOADS

Name	File type	
 <b>Product sheet - CARRIER SLIDING DOOR x2_ENG.pdf</b>	Product sheets	 <b>DOWNLOAD</b>

## ACCESSORIES



BRACKETS FOR  
SAFETY SWITCHES




EURO CYLINDER  
LOCK


## COMBINE WITH




POST 80X80



PANEL ST30



POST 60X40



PANEL ST20

## IMAGES

