



Access control

The Nylofor swing gates are available in single and double version with Nylofor infill as a perfect combination with Nylofor panel fences.

Nylofor[®] swing gates

BENEFITS

Rigid construction

All elements of the Nylofor swing gates are of an extremely rigid construction: frame, Nylofor panels and post system.

Optimal setting

The locking system allows optimal setting and is easy to install.

Fully adjustable hinges

The hinges are adjustable and allow each leaf to swing through 180°.

High quality coating

The Nylofor swing gates receive the best coating that exists today.

Rapid installation

The Nylofor swing gates are designed for quick installation: the accessories are limited to a minimum.

Secure adjustable lock

External lock with secure adjustable closing.

Applications

- Factories and workshops
- Administrative centres
- Public buildings
- Play- and sport grounds
- Schools
- Parks
- Airports
- Military sites



Frame

Frame out of square tube 40 x 60, 60 x 60 or 80 x 60 mm, with welded Nylofor infill.

Posts



Square posts out of welded tube with cap.
Optional: welded fence connection strip or fence connection clips.

Accessories

Hinges: adjustable, allow the gate wings to open through 180°.

Lock system: external secure lock system, with adjustable closing.

Ground bolt: manufactured from stainless steel and attached to the wing, to be anchored into the central floor plate.

Standard on double swing gate: 1 ground bolt

Additional ground bolt for single or double gates: optional.

CE Marked

Nylofor gates are CE marked according to the European directive: Construction products directive (89/106/CE) and type tested according to standard EN 13241-1 for Industrial, commercial and garage doors and gates.



Coating technique

Galvanised and polyester coated.

Colours (p 116)

Green RAL 6005, white RAL 9010, black RAL 9005

Other colours on request.

Options



Gate catcher



Ground stop



Fence connection strip



Fence connection clip



Ground bolt



Ground stop with slam plate



Dust cover for lock

ASSORTMENT SINGLE SWING GATES NYLOFOR 3D

Width (mm)	Height (mm)	Free passage (mm)	Overall width (mm)
1000	1030/1230/1530/1730/2030/2430	985	1145
1200	1030/1230/1530/1730/2030/2430	1255	1415
1500	1030/1230/1530/1730/2030/2430	1525	1685/1725*
2000	1030/1230/1530/1730/2030/2430	2065	2265
2500	1030/1230/1530/1730/2030/2430	2470	2670/2750**
3000	1030/1230/1530/1730/2030/2430	3010	3210/3290***
4000	1030/1230/1530/1730/2030/2430	3955	4235/4275*
4500	1030/1230/1530/1730/2030/2430	4495	4775/4815**
5000	1030/1230/1530/1730/2030/2430	5070	5350/5390****

ASSORTMENT DOUBLE SWING GATES NYLOFOR 3D

Width (mm)	Height (mm)	Free passage (mm)	Overall width (mm)
2000	1030/1230/1530/1730/2030/2430	1930	2090
2400	1030/1230/1530/1730/2030/2430	2470	2630
3000	1030/1230/1530/1730/2030/2430	3010	3170/3210*
4000	1030/1230/1530/1730/2030/2430	4090	4290
5000	1030/1230/1530/1730/2030/2430	4900	5100/5180**
6000	1030/1230/1530/1730/2030/2430	5980	6180/6260***
8000	1030/1230/1530/1730/2030/2430	7870	8150/8190*
9000	1030/1230/1530/1730/2030/2430	8950	9230/9270**
10000	1030/1230/1530/1730/2030/2430	10100	10380/10420****

* height: 2430

** heights: 2030 - 2430

*** heights: 1530 - 1730 - 2030 - 2430

**** heights: 1730 - 2030 - 2430

ASSORTMENT SWING GATES NYLOFOR F, 2D AND 2D SUPER

Width (mm)	Height (mm)	Free passage (mm)	Space needed fixing strip included (mm)
Single gates			
1000	1030/1230/1430/1630/1830/2030/2430	920	1110
Double gates			
3000	1030/1230/1430/1630/1830/2030/2430	2900	3090
4000	1030/1230/1430/1630/1830/2030/2430	3900	4090/4130*
5000	1030/1230/1430/1630/1830/2030/2430	4900	5170
6000	1030/1230/1430/1630/1830/2030/2430	5960	6230
8000 or 10000	1630/1830/2030/2430	on request	on request

Other dimensions on request - * for heights: 1830 - 2030 mm

