



## Robusta® SQ25 swing gate

### Access control

Single and double Robusta SQ25 swing gates with tubular infill, adapted posts, hinges, lock- and ground bolt system.

### Product detail



### **BENEFITS**

#### **Rigid construction**

All elements of the Robusta SQ25 swing gates are of an extremely rigid construction: frame, tubes and post system.

#### **Security**

The distance between the vertical bars is 110 mm, complying to the highest safety standards.

#### **Optimal setting**

The locking system allows optimal adjustment and is easy to install.

#### **Universal opening**

The hinges are adjustable and allow each gate wing to swing through 180°. All hinges are positioned symmetrically.

#### **High quality coating**

The Robusta SQ25 swing gates receive high quality coating.

#### **Quick installation & exchangeability**

The Robusta SQ25 swing gates are designed for quick installation: the accessories are limited to a minimum.

### Applications



### Functionalities





### Frame

Frame out of profile tube 60 x 40 or 60 x 60, with bars of 25 x 25 mm, mitre welded in the frame at a distance of 110 mm.

### Posts

Square posts out of welded tube with cap.  
Optional: welded fence connection strip or fence connection clips for the attachment of the panels to the gate posts by means of specific connection strips.

### Components

- **Hinges:** adjustable, allow the gate wings to open through 180°.
- **Lock system:** external secure lock system, with adjustable latch.
- **Ground bolt:** manufactured from stainless steel and attached to the wing, to be anchored into the central floor plate.
  - Standard on double swing gate: 1 ground bolt
  - Additional ground bolt for single or double gates: optional.
- **Ground stop** will be delivered with double gate.

### CE Marked

Robusta SQ25 swing gates are CE marked according to the European regulation: Construction products regulations (CPR) (EU-305/2011) and type tested according to standard EN 13241-1 for industrial, commercial, garage doors and gates.



### Coating technique

Galvanised and polyester coated (min. 100 microns).

### Colours

Green RAL 6005, white RAL 9010, black RAL 9005  
Hot dip galvanised finish available.

### Options



Gate catcher



Fence connection strips



Fence connection clip



Ground bolt



Ground stop  
with slam plate



Dental strip

### ASSORTMENT OF ROBUSTA SQ25 SINGLE SWING GATES

Width mm	Height mm	Free passage mm	Overall width mm
1000	1030/1230/1530/1730/2030/2430	985	1145
1200	1030/1230/1530/1730/2030/2430	1255	1415
1500	1030/1230/1530/1730/2030/2430	1525	1685/1725*
2000	1030/1230/1530/1730/2030/2430	2065	2265
2500	1030/1230/1530/1730/2030/2430	2470	2670/2750**
3000	1030/1230/1530/1730/2030/2430	3010	3210/3290***
4000	1030/1230/1530/1730/2030/2430	3955	4235/4275*
4500	1030/1230/1530/1730/2030/2430	4495	4775/4815**
5000	1030/1230/1530/1730/2030/2430	5070	5350/5390****

### ASSORTMENT OF ROBUSTA SQ25 DOUBLE SWING GATES

Width mm	Height mm	Free passage mm	Overall width mm
2000	1030/1230/1530/1730/2030/2430	1930	2090
2400	1030/1230/1530/1730/2030/2430	2470	2630
3000	1030/1230/1530/1730/2030/2430	3010	3170/3210*
4000	1030/1230/1530/1730/2030/2430	4090	4290
5000	1030/1230/1530/1730/2030/2430	4900	5100/5180**
6000	1030/1230/1530/1730/2030/2430	5980	6180/6260***
8000	1030/1230/1530/1730/2030/2430	7870	8150/8190*
9000	1030/1230/1530/1730/2030/2430	8950	9230/9270**
10000	1030/1230/1530/1730/2030/2430	10100	10380/10420****

\* height: 2430 mm

\*\* heights: 2030 - 2430 mm

\*\*\* heights: 1530 - 1730 - 2030 - 2430 mm

\*\*\*\* heights: 1730 - 2030 - 2430 mm.

