



SURFACE MOUNTED ELECTROMAGNETIC LOCK WITHOUT INTEGRATED HANDLES

Item No. MAGMAG-

Screw-on magnetic lock without handle. Available in 2 versions. MAGMAG3000 with 660 lbs and MAGMAG6000 with 1320 lbs of pulling force. The aluminum powder coated housing equipped with the unique Quick-Fix fixations ensures a fast and nicely finished mounting. Eliminate time-consuming welding; drilling 5 holes is enough to fix the lock. A two-layer, protective coating guarantees that our electromagnetic locks are ready for years of worry free use outside.



SPECIFICATIONS

Specifications

- 500h salt spray resistant! SGS certified (ISO 9227)
- Special two-layer protective coating developed for outdoor use
- SGS Certified
- Powder coated aluminium housing
- Anti-residual magnetism kick-off system
- Raised edge on the magnet housing makes it impossible to put a crowbar between the magnet and the armature plate
- Fail open
- Fast and easy fixing by means of 5 holes with Quick-Fix
- Current MAGMAG3000: 500 mA / 12 V or 250 mA / 24 V
- Current MAGMAG6000: 460 mA / 12 V or 230 mA / 24 V
- Voltage: 12V / 24V DC
- MAG3000: Minimal pulling force: 3000N (300 kg)
- MAG6000: Minimal pulling force: 6000N (600 kg)
- Guaranteed holding force tested on every magnetic lock

Available in following RAL-colours



ZILV RAL 6005 RAL 9005





Subscribe to push notifications



