

Machine guard door

The single telescopic door can be built with our mesh or polycarbonate panels to fit your chosen machine guard system. Two telescopic rails located at the top and the bottom of the door blade increases the stability and creates an opening with a free access in height. Use the standard panel heights 2050 mm or 1250 mm in the various widths up to 1500 mm to create your requested size. The doors can be ordered partly pre-assembled from factory, or as separate panels, posts and door kit for assembly on site.

With the single telescopic sliding door you can build a door opening from 800-1500 mm.

Depending on the risk assessment, you choose the suitable lock for your door.



FACTS

Door dimensions, system height 1400 mm


Panel height (mm)	Panel width (mm)	Opening width (mm)
1250	800	760
1250	1000	960
1250	1200	1160
1250	1500	1460

Door dimensions, system height 2200 mm

Panel height (mm)	Panel width (mm)	Opening width (mm)
2050	800	760
2050	1000	960
2050	1200	1160
2050	1500	1460

Standard colour for posts are grey RAL7037, black RAL9005 or yellow RAL1018. Standard for mesh panels are RAL 7037 and RAL 9005.

Doors can be made in the colour of your choice.



LOCK OPTIONS

Cylinder Lock (Kit 5780)



Safe Lock (Kit 5030)



Safe Lock ES (Kit 5040)

